

CAT 6A KVA Keystone Jack

KVA Series component-rated RJ45 90 degree Unshielded Keystone jack keystone jack is designed to easily snap in and out of the wall outlet, patch panel and surface mount box.

It is individually terminated using Insulation Displacement Connectors (IDC) with punch down tool for quick installation.

KVA Series UTP Cat 6A keystone jack comes with T568A/T568B color label and fully complies with connecting hardware transmission performance of edition 2.2 of ISO/IEC 11801 2.2 edition, CENELEC 50173-1 cabling requirements for Category 6A & Category 6A components performance, and ANSI/TIA-568-C.2 for Return loss, Insertion loss, NEXT loss, FEXT loss, TCL, TCTL, PSANEXT loss, and PSAFEXT loss up to 500MHz.

Performance: **KVA Series** completely contains all performance level from Cat 5e, Cat 6 to Cat 6A.Press-Fit Technology: Makes the product more reliable. It also has a better quality of conductivity. A more stable transmission performance is guaranteed since there is no other medium that takes effect in between PCB and contacts

MODEL	KVA-6A-XX (XX indicates color)
Category	6A
Contacts	8
Bandwidht	Up to 500MHz
Connection Type	IDC (Insulation Displacement) ETL Verfied
Termination	T568A/T568B
Description	TliA/EIA Category 6A UTP Punchdown Keystone Jack, 110 IDC
Available Colors	White (WH), Black (BK), Red (RD), Blue (BL)

















Features

- Lead Free
- RoHS compliant
- ETL Verified Connecting Hardware
- ANSI/TIA-568-C.2
- ANSI/TIA-568-B.2-10
- ISO/IEC 11801 2.2
- CENELEC EN 50173-1
- CE compliant
- ANSI/TIA-1096-A
- FCC Part 68
- IEC 60603-7-2
- IEC 60603-7-4
- IEC 60603-7-41
- Temperature: -10°C~60°C
- Humidity: 10%~90% RH