

FK are Fiber Optic Fan Out Kits offers a modular design, compact and exible, allows the adjustment of the arms without need for special equipment or tools.

Provides protection to the bu of 250µm, in addition to enlarge it to 900µm

The tubes have a length of 1.2 m, the color of each tube is according to the ANSI / TIA-598 standard distribution and administration of optic fibers.

- Allows to enlarge the buffer from 250µm to 900µm.
- Compatible with multimode or single mode fibers.
- Modular design, compact, flexible and easy to install.
- The color code corresponds to ANSI / TIA-598
- Provides durable fiber protection.
- Tube Length: 1.20 meters
- Tube Diameter accomodates cables from 6.5 to 10.5 mm
- You can make splices or connectorize the fiber.
- No special tools are required for installation.



Features

- **RoHS compliant**
- **GR326-CORE**
- **TIA/EIA 310-D**
- **CEA 310**
- **ANSI/TIAI/EIA 568B.2**
- **ANSI/ICEA S-102-700**
- **DIN 41494-7**
- **ISO/IEC 11801**
- **DIN 41494-8**
- **NEMA WC66**
- **IEC 60297**
- **EN 50173-1**
- **IEC 60297-3-100**
- **IEC 60297-3-101**
- **IEC 60297-3-102**
- **IEC 60297-3-103**
- **IEC 60297-3-104**
- **IEC 60297-3-105**
- **TIA/EIA 598**
- **Temperature: -55°C~100°C**
- **Humidity: 0%~95% RH**

MODEL	DESCRIPTION
FK06	6 Fiber Fan Out Kit, 1.20 meters length Diameter cables from 6.5 to 10.5 mm
FK12	12 Fiber Fan Out Kit, 1.20 meters length Diameter cables from 6.5 to 10.5 mm
SS60	60 mm splice sleeve/ 10 mm